PRODUCT DATA SHEET

RHINO SHRINK WRAP 10m × 50m 200ST

rhinoshrinkwrap.com

DESCRIPTION

Rhino Shrink Wrap® 200ST is a premium-grade UV stabilised LDPE shrink film designed to provide durable weather protection during product storage and transport. Engineered for excellent shrink performance, high tear resistance and long-term outdoor durability, it is ideal for wrapping machinery and equipment, modular buildings, boats and other valuable assets. Manufactured in ISO 9001-certified facilities, every roll shrinks evenly, welds easily and forms a tough, weather-resistant protective enclosure.



CERTIFICATIONS

- Factory is an ISO 9001 : 2008 certified company by DNV GL

PRODUCT INFORMATION

PROPERTY	VALUE
Product	Standard Grade Shrink Wrap Film
Product Code	5050
Film Width	10 m
Roll Length	50 m
Folded Width	1600 mm
Thickness	200 µm
Material	LDPE
Structure	Co-extruded 3 Layer
Colour	White
Rolls per Pallet	up to 9
UV Stability	12 months
Application Temperature	-55°C to +55°C
Recyclability	100% Recyclable LDPE

TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	RESULT
Average Thickness	ISO 4591	200 ±10% µm
Spot Thickness	ISO 4593	200 ±15% µm
Tensile stress at break		
MD	ASTM D882	19 ±10% N/mm^2
TD	ASTM D882	12 ±10% N/mm^2
Elongation at break		
MD	ASTM D882	520 ±10%
TD	ASTM D882	570% ±10%
Dart Drop Test	ISO 7765/1	600g ±10%
Shrink		
MD	at 180°C	60%
TD	at 180°C	15%
Density	ISO 1183	0.93 g/cm^3

NOTE

The information in this datasheet is believed to be accurate at the time of publication and is provided for guidance only. Unless otherwise stated, all values shown are typical. Rhino Shrink Wrap® reserves the right to amend product specifications without notice. Users are responsible for determining the suitability of the product for their intended application.

Doc. No: DAT-WRA-015 Revison: 1.0 Date: 03. 07. 2026