PRODUCT DATA SHEET

RHINO SHRINK WRAP TAPE – 33m ROLL

DESCRIPTION

Rhino Shrink Wrap Tape, commonly referred to as 'patch tape', is a tough, polyethylene-backed tape with a specially formulated all-weather adhesive. It bonds reliably even in low temperatures and after extended exposure to sunlight—ideal for demanding outdoor applications.



TYPICAL APPLICATIONS

- Repairing small holes in shrink wrap sheeting (e.g. heat shrink damage)
- Sealing joins between two sheets of shrink wrap
- Maintaining a seal around protrusions passing through the sheeting
- Securing zipped access doors in place

PRODUCT INFORMATION

PROPERTY	VALUE
Total Thickness	0,2mm
Standard Sizes	100mm × 33m, 200mm × 33m
Breaking load	27N/cm
Elongation	400%
Adhesion – Steel	3.5N/cm
Adhesion – Self	3.0N/cm
RoHS Compliant	Yes
Service Temperature	-5˚C to +50˚C
Application Temperature	0˚C to +40˚C
Storage Temperature	+12˚C to +25˚C
Standard Shelf Life	24 months from date of manufacture (at 25°C)

NOTE

The information in this datasheet is believed to be accurate at the time of publication and is provided for guidance only. Unless otherwise stated, all values shown are typical. Rhino Shrink Wrap® reserves the right to amend product specifications without notice. Users are responsible for determining the suitability of the product for their intended application.

Doc. No: DAT_TAP_001 Revison: 1.0 Date: 03. 07. 2026