PRODUCT DATA SHEET

RHINO SHRINK WRAP TAPE – 55m ROLL

DESCRIPTION

Rhino Shrink Wrap Tape, commonly referred to as 'patch tape', is a heavy duty polyethylene-backed tape with a specially formulated all-weather adhesive. It bonds securely, even at low temperatures or after prolonged exposure to sunlight, making it ideal for reliable, long-lasting repairs and sealing. Supplied in a 55m roll for fewer roll changes during larger projects.



TYPICAL APPLICATIONS

- Repairing small holes in shrink wrap sheeting (e.g. heat shrink damage)
- Sealing joins between two sheets of shrink wrap
- Maintaining a seal around protrusions passing through the sheeting
- Securing zipped access doors in place

PRODUCT INFORMATION

PROPERTY	VALUE
Backing	Polyethylene Film
Adhesive	Synthetic Rubber
Liner	N/A
Colors	White
Specifications	N/A
Standard Sizes	96mm x 55m
Storage Temperature	+12˚C to +25˚C
Standard Shelf Life	24 months from date of manufacture (at 25°C)

TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	VALUE
Total Thickness	ASTM D-1000	0.229 mm
Adhesion to Steel	PSTC-101	9.30 N/cm
Adhesion to Backing	PSTC-101	4.38 N/cm
Tensile Strength	ASTM D-1000	52.54 N/cm
Application Temperature		-1 to 71°C
Operating Temperature		-7 to 93°C
Elongation		65%

NOTE

The information in this datasheet is believed to be accurate at the time of publication and is provided for guidance only. Unless otherwise stated, all values shown are typical. Rhino Shrink Wrap® reserves the right to amend product specifications without notice. Users are responsible for determining the suitability of the product for their intended application.

Doc. No: DAT_TAP_002 Revison: 1.0 Date: 03. 07. 2026